

Assembly & Installation Guidelines Built-in Wardrobe — Galleria BIR08

Please read these guidelines carefully before installing and using the product.

SAFETY INFORMATION

- Always wear appropriate safety equipment.
- This product requires two people for installation.
- If this product falls down, serious or fatal crushing injuries can occur. This product should be permanently fixed to the wall – contact your local fastening device retailer for advice on what fastening devices are suitable for your walls.
- Assembly should be carried out by an appropriately skilled person, due to the risk of wrongful assembly leading to injury or damage.



ITEMS INCLUDED IN THE BOX

TOWER SHELL BOX x 2

16 x cams
20 mm diameter

1 x deck
575 mm W x 447 mm H x 16 mm D

16 x cam bolts
16 mm H x 6 mm diameter

2 x drawer tower sides
2000 mm W x 447 mm H x 16 mm D

1 x shelf nailer
575 mm W x 95 mm H x 16 mm D

1 x front toe
575 mm W x 95 mm H x 16 mm D

2 x nailers
575 mm W x 95 mm H x 16 mm D

1 x fixed shelf
575 mm W x 447 mm H x 16 mm D

16 x adjustable shelf pins
10 mm W x 14 mm H x 13 mm D

TOP SHELF BOX

1 x top shelf
Up to 3000 mm W x 447 mm H x 16 mm D

1 x back cleat
Up to 3000 mm W x 95 mm H x 16 mm D

1 x hanging rail
3000 mm W x 35 mm diameter

2 x side cleats
425 mm W x 95 mm H x 16 mm D

Fast caps (white dots)
14 mm diameter

8 x hanging rail screws
16 mm H x 6 mm diameter

4 x hanging rail brackets
45 mm H

1 x sharkfin support bracket
300 mm W x 300 mm H

ADJUSTABLE SHELVES BOX x 2

2 x adjustable shelves
575 mm W x 447 mm H x 16 mm D

DRAWER RUNNERS BOX x 2

4 x drawer side (left)
400 mm W x 175 mm H x 14 mm D

4 x drawer side (right)
400 mm W x 175 mm H x 14 mm D

4 x drawer runner clip (left)
103 mm W x 53 mm H x 17 mm D

4 x drawer runner clip (right)
103 mm W x 53 mm H x 17 mm D

4 x drawer front clip (lower)
54 mm W x 40 mm H x 7 mm D

4 x drawer front clip (upper)
52 mm W x 62 mm H x 11 mm D

4 x drawer side cover cap (bottom)
44 mm W x 17 mm H x 1 mm D

4 x drawer side cover cap (top)
44 mm W x 12 mm H x 1 mm D

4 x drawer runner (left)
400 mm W x 47 mm H x 47 mm D

4 x drawer runner (right)
400 mm W x 47 mm H x 47 mm D

4 x drawer rear bracket
30 mm W x 11 mm H x 15 mm D

drawer screw #1
6G x 16 mm CSK

drawer screw #2
6G x 13 mm CSK

drawer screw #3
6G x 14 mm CSK

drawer screw #4
6G x 10 mm CSK

34 x Euro screw

BACKS, BASES AND FRONT BOX x 2

4 x drawer bases
556 mm W x 390 mm H x 16 mm D

4 x drawer backs
535 mm W x 148 mm H x 16 mm D

4 x drawer fronts
602 mm W x 253 mm H x 16 mm D

HANDLES BOX

8 x drawer handles

8 x drawer handle bolts
47 mm H x 5 mm diameter

EXTRA ITEMS AND TOOLS REQUIRED CHECKLIST

These items are readily available from all major hardware stores.

Drill and No.2 Phillips head driver <input type="checkbox"/>	Builder's square <input type="checkbox"/>
Multi tool <input type="checkbox"/>	Countersink drill bit <input type="checkbox"/>
Stepladder <input type="checkbox"/>	Hammer <input type="checkbox"/>
Phillips head screwdriver <input type="checkbox"/>	Liquid Nails <input type="checkbox"/>
Spirit level <input type="checkbox"/>	Gapping <input type="checkbox"/>
Measuring tape and pencil <input type="checkbox"/>	Packers <input type="checkbox"/>
Circular saw <input type="checkbox"/>	6-gauge 40 mm screws <input type="checkbox"/>
Silicone/caulking gun <input type="checkbox"/>	6-gauge 13 mm screws <input type="checkbox"/>
Stud finder <input type="checkbox"/>	6-gauge 28 mm screws <input type="checkbox"/>
3 mm drill bits <input type="checkbox"/>	Wallmates <input type="checkbox"/>

IMPORTANT BUILDING TERMINOLOGY


In construction, tradespeople use terms like 'square', 'level' and 'plumb' to be sure that their measurements are accurate, and the finished project is successful. Here are some definitions of common building terminologies.

- Square:** when corners are 90 degrees.
- Level:** straight from side to side, like a shelf that's been properly installed.
- Plumb:** straight up and down, like the walls of a building.
- Flush:** when two adjoining surfaces are perfectly flat next to each other.
- Skirting:** a board that runs along the border between the interior wall and the floor.
- Architrave:** is used to frame windows and openings to conceal any shrinkage or movement that may occur between the wall and the casing within the door surround.
- Jamb:** is a flat surface that runs vertically on each side of the door frame.
- Scribe:** cutting away the waste material that is preventing two materials from meeting together perfectly.

IMPORTANT INFORMATION


- Pre-drill board and countersink before fixing to walls.
- Read guidelines carefully before commencing.

Step 1




Open tower shell box.
 Screw in cam bolts into drawer tower sides (both sides).

Step 2




Hammer cams into nailers, toe, deck and fixed shelf.

Step 3




Place nailers over cam bolts and tighten.
 Place deck over cam bolts and tighten.
 Place fixed shelf over cam bolts and tighten.

Step 4




Place side on top over cam bolts and tighten cams.

Step 5




Open drawer, runners box and backs bases and fronts box.
 Layout all parts to assemble drawers.

Step 6




Fix runners L (B) and R (H) to tower sides, screwing euro screw into third hole in top row (Exploded image).

Step 7




Slide drawer sides A and G into drawer base.
Slide drawer back to the inside of the brackets.

Step 8




Secure drawer back to bracket using screw.
Drawer screw – 6Gx13 mm CSK (10)

Step 9




Fix bracket M and D to drawer fronts.
Drawer screw – 6Gx16 mm CSK (8)
Open handles box.
Fit handle to the drawer front.

Step 10




Engage drawer front to drawer sides.
(click sound include)
Fit cover plates L and E.

Step 11




Screw drawer sides to drawer base.

Step 12




Screw adjustment brackets C and K
to drawer base.
Drawer screw – 6Gx16 mm CSK (6)

Step 13




Fully extend runner. Place drawer on runner
and push drawer all the way in until you hear
a click.
Drawer is now engaged to runner.

Step 14




Drawer adjustment:
Align drawers using the up down to the side adjustment.
1a tilt drawer up and down at back.
1b and 1c moves laterally.
1d moves drawer up or down.

Step 15



If required, to remove the drawer, extend the drawer, place hands under drawer, locating the brackets on each side and push levers in on drawer. This will release, lifting drawer off runner.

Step 16




Check wall for plumb, place level on wall.
If wall greater than 3 mm out of plumb, scribe infill.

TIP: Refer to our guide – How to scribe infill.
All our guides are located at:
stegbar.com.au/support


If required, using the 6 x 28 6-gauge screws, screw 16 mm infill to wall side of shelf unit flush with the front.
Screw infill to side of tower if required from front or back.

Step 17




Measure the width and depth of towers and mark skirting with pencil (be sure to include the infill if infill required).

Step 18



Use multi tool to cut and remove skirting where towers are to be installed.

Step 19




Pre-drill 2 x 3 mm holes into tower nailer.
Place towers in position. Place level on towers to ensure level and plumb.
Mark wall with pencil.
Fix 40 mm screw into stud – if stud is not present, then fix with screw and plug (wallmate).

TIP: Use packers to level tower.


TIP: Pre-drill board and countersink.

Step 20



Use spirit level to mark horizontal line from top of shelf unit across full width of rear wall for back cleat and side cleat positioning.
Locate wall studs with stud finder and mark wall above pencil line (no greater than 16 mm).


Step 21



Measure distance between towers.
Cut back cleat to size.
Apply liquid nails to back of cleat in
radio wave pattern and screw cleat
to wall into stud.

TIP: Pre-drill board and countersink.


Step 22



Open Top Shelf box.
Measure top shelf width ensuring you check
the walls are square using a square edge.
Cut top shelf to correct size allowing for wall
run outs.
Place top shelf into position. Screw top shelf
down into wall cleats using 40 mm screws.

TIP: Pre-drill board and countersink.


Step 23



Measure 214 mm off cleat on back wall and 80mm down from side cleat, thus measurement is to the bottom hole of hanging rod end.

Fix hang rail ends using 16 mm screws.

Step 24




Measure distance between towers and deduct 6 mm off overall width.

Cut hang rail to size and insert into hanging rail end ends.

TIP: Face top hang rail with groove up.

Step 25




Hanging rail sharkfin support must be screwed into a stud.

Push sharkfin support into wall cleat, making sure sharkfin is plumb and square with back cleat.


Screw sharkfin support into back cleat and top shelf with 13 mm screws and 40 mm screw into wall stud.

Step 26



Using caulking, gap all connections between board and wall or board and board.

Step 27



Install adjustable shelves.


Place shelf pins into tower at desired heights.

Place shelf on pins.

Assembly & Installation Guidelines

Built-in Wardrobe — Galleria BIR08

Step 28



Fast cap (white dot) all screws.

Clean shelving with damp cloth and remove stickers.



Stegbar is not providing any installation of the product, which is your responsibility. The information in this assembly document is of a general nature only and is provided regarding a typical installation process. Accordingly, this assembly document does not take into account your specific circumstances, environment, needs, tools or skills.

You should not rely solely on the general information in this assembly document for installation. There are risks associated with installation and you assume those risks voluntarily by installing this product. To the extent permitted by law, Stegbar does not accept responsibility and is not liable for any loss, damage or injury suffered by you as a result of any circumstances specific to you that are not addressed in these assembly documents.

You should independently consider whether the services of any third party are appropriate for you. Any service supplied by a third party is subject to the terms and conditions of that third party. Stegbar is not responsible for any agreements, maintenance, delivery or satisfaction of any transactions undertaken with a third-party provider. To the extent permitted by law, Stegbar is not responsible and is not liable for any loss, damage or injury suffered by you as a result of the conduct of the third party.

Stegbar reserves the right to alter or amend without prior notice general information and design details specified in these assembly documents.
JWSNAT0575/0423 | stegbar.com.au | Version 1.0 | October 2023